September 08, 2011 Chapter 4 **PART IV CLASSFUL INTERNET ADDRESSES**

Internetworking With TCP/IP

Definitions

- Name
 - Identifies *what* an entity is
 - Often textual (e.g., ASCII)
- Address
 - Identifies where an entity is located
 - Often binary and usually compact
 - Sometimes called locator
- Route
 - Identifies how to get to the object
 - May be distributed

Internetworking With TCP/IP

Internet Protocol Address (IP Address)

- Analogous to hardware address
- Unique value assigned as unicast address to each host on Internet
- Used by Internet applications

Internetworking With TCP/IP

IP Address Details


- 32-bit binary value
- Unique value assigned to each host in Internet
- Values chosen to make routing efficient


Internetworking With TCP/IP


IP Address Division


- Address divided into two parts
 - Prefix (network ID) identifies network to which host attaches
 - Suffix (host ID) identifies host on that network

Internetworking With TCP/IP









Classful Addressing

- Original IP scheme
- Explains many design decisions
- New schemes are backward compatible

Internetworking With TCP/IP

Desirable Properties Of An Internet Addressing Scheme

- Compact (as small as possible)
- Universal (big enough)
- · Works with all network hardware
- Supports efficient decision making
 - Test whether a destination can be reached directly
 - Decide which router to use for indirect delivery
 - Choose next router along a path to the destination

Internetworking With TCP/IP


Division Of Internet Address Into Prefix And Suffix

- How should division be made?
 - Large prefix, small suffix means many possible networks, but each is limited in size
 - Large suffix, small prefix means each network can be large, but there can only be a few networks
- Original Internet address scheme designed to accommodate both possibilities
 - Known as classful addressing

Internetworking With TCP/IP

Original IPv4 Address Classes

Three Principle Classes



Class A Addresses are used for the handful of networks that have more than 2^{16} (i.e. more than 65,536) hosts.

- · 7 Bits for netid
- · 24 Bits for hostid




Class B Addresses are used for intermediate size networks that have up to 2¹⁶ (i.e. up to 65,536) hosts.

- · 14 Bits for netid
- · 16 Bits for hostid

Internetworking With TCP/IP

Original IPv4 Address Classes


Three Principle Classes




Class C Addresses are used for networks that have less than 28 (i.e. less than 256) hosts.

- 21 Bits for netid
- 8 Bits for hostid

Internetworking With TCP/IP



Internetworking With TCP/IP



7F2EHD

Important Property

- Classful addresses are self-identifying
- Consequences
 - Can determine boundary between prefix and suffix from the address itself
 - No additional state needed to store boundary information
 - Both hosts and routers benefit

Internetworking With TCP/IP

Endpoint Identification

Because IP addresses encode both a network and a host on that network, they do not specify an individual computer, but a connection to a network.

Internetworking With TCP/IP

IP Address Conventions

- When used to refer to a network
 - Host field contains all 0 bits
- Broadcast on the local wire
 - Network and host fields both contain all 1 bits
- Directed broadcast: broadcast on specific (possibly remote) network
 - Host field contains all 1 bits
 - Nonstandard form: host field contains all 0 bits

Internetworking With TCP/IP

Assignment Of IP Addresses



- All hosts on same network assigned same address prefix
 - Prefixes assigned by central authority
 - Obtained from ISP
- Each host on a network has a unique suffix
 - Assigned locally
 - Local administrator must ensure uniqueness

Internetworking With TCP/IP

Advantages Of Classful Addressing

- Computationally efficient
 - First bits specify size of prefix/suffix
- Allows mixtures of large and small networks

Internetworking With TCP/IP

Directed Broadcast

IP addresses can be used to specify a directed broadcast in which a packet is sent to all computers on a network; such addresses map to hardware broadcast, if available. By convention, a directed broadcast address has a valid netid and has a hostid with all bits set to 1.

Internetworking With TCP/IP

Limited Broadcast

- All 1's
- Broadcast limited to local network only (no forwarding)
- Useful for bootstrapping

Internetworking With TCP/IP

All Zeros IP Address

- Can only appear as source address
- Used during bootstrap before computer knows its address
- Means "this computer

Internetworking With TCP/IP

Internet Multicast

- IP allows Internet multicast, but no Internet-wide multicast delivery system currently in place
- Class D addresses reserved for multicast
- Each address corresponds to group of participating computers
- IP multicast uses hardware multicast when available
- More later in the course


Internetworking With TCP/IP

Consequences Of IP Addressing

- If a host computer moves from one network to another, its IP address must change
- For a multi-homed host (with two or more addresses), the path taken by packets depends on the address used

Internetworking With TCP/IP

Multi-Homed Hosts And Reliability



- Knowing that B is multi-homed increases reliability
- If interface I₃ is down, host A can send to the interface I₅

Internetworking With TCP/IP

Dotted Decimal Notation

- Syntactic form for expressing 32-bit address
- Used throughout the Internet and associated literature
- Represents each octet in decimal separated by periods (dots)

Internetworking With TCP/IP

Example Of Dotted Decimal Notation

• A 32-bit number in binary

10000000 00001010 00000010 00000011

The same 32-bit number expressed in dotted decimal notation

128.10.2.3

Internetworking With TCP/IP

Loopback Address

- Used for testing
- Refers to local computer (never sent to Internet)
- Address is 127.0.0.1

Internetworking With TCP/IP


Classful Address Ranges

Class	Lowest Address	Highest Address
Α	1.0.0.0	126.0.0.0
В	128.1.0.0	191.255.0.0
С	192.0.1.0	223.255.255.0
D	224.0.0.0	239.255.255.255
E	240.0.0.0	255.255.255.254


Internetworking With TCP/IP

Summary Of Address Conventions This host 1 all 0s Host on this net 1 all 0s host Limited broadcast (local net) 2 all 1s Directed broadcast for net 2 net all 1s Loopback³ anything (often 1) 127 Notes: 1 Allowed only at system startup and is never a valid destination address. ² Never a valid source address. ³ Should never appear on a network.

Internetworking With TCP/IP



Internetworking With TCP/IP




Internetworking With TCP/IP

Another Addressing Example

- Assume an organization has three networks
- Organization obtains three prefixes, one per network
- Host address must begin with network prefix

Internetworking With TCP/IP



Internetworking With TCP/IP

Summary

- IP address
 - 32 bits long
 - Prefix identifies network
 - Suffix identifies host
- Classful addressing uses first few bits of address to determine boundary between prefix and suffix

Internetworking With TCP/IP

Summary (continued)

- Special forms of addresses handle
 - Limited broadcast
 - Directed broadcast
 - Network identification
 - This host
 - Loopback

Internetworking With TCP/IP