

# Spring 2019 CMP 168 Final Exam V1

124 points total

Name: \_\_\_\_\_

Date: \_\_\_\_\_

(24 points / 2 points each) Trace the code and write the result (Write ERROR if there is an ERROR)

	Code	Method Call	Results
1	<pre> public static int q1(int a, int b) {     if (a == 0) {         return b;     } else if (a &lt; 0) {         return b + 3;     } else {         return q1(a - b, b * 2);     } }                     </pre>	q1(4, 2);	
		q1(6, 2);	
		q1(14, 6);	
		q1(12, 4);	
2	<pre> public static void q2(boolean a,                     boolean b,                     boolean c) {     if (a &amp;&amp; b &amp;&amp; !c) {         System.out.println("right");     } else if (a &amp;&amp; c) {         System.out.println("high");     } else if (b &amp;&amp; c) {         System.out.println("low");     } else if ((a    !b) &amp;&amp; c) {         System.out.println("wrong");     } else {         System.out.println("in");     } }                     </pre>	q2(true, false, true);	
		q2(false, false, true);	
		q2(false, true, true);	
		q2(true, true, false);	
3	<pre> public static void q3(char[] chars,                     int i,                     int j,                     char c) {     int index = (i * j) % 6;     try {         chars[index] = c;         System.out.println("Success!" + c);     } catch (IndexOutOfBoundsException e) {         System.out.println("No Good!");     } catch (NullPointerException e) {         System.out.println("Really Bad!");     } }                     </pre>	char[] a = {'a', 'e', 'i', 'o', 'u'}; q3(a, 2, 5, 'c');	
		char[] a = {'a', 'b', 'c', 'd'}; q3(a, 7, 5, 'o');	
		char[] a = {'x', 'y', 'z'}; q3(a, 8, 4, 'w');	

		<pre>char[] a = null; q3(a, 8, 4, 'w')</pre>	
--	--	--	--

4 (25 points / 5 points each) Create the Java class **Animal** that has the following **private** attributes:

Attribute	name : String	numLegs : int	gender : char
-----------	---------------	---------------	---------------

a. Create a **default constructor** that initializes all 3 attributes to the following values

Attribute	name	numLegs	gender
Default Value	"unknown"	0	'u'

b. Create an **overloaded constructor** that takes in values for all 3 attributes and assigns them.

c. Create **getter** and **setter** methods for all 3 attributes.


Getters	Setters
---------	---------

--	--

- d. Create the **equals** method. Two **Animal** objects are equal when their **numLegs** and **gender** are the same. (Disregard the names)

--

- e. Create the **toString** method so that it returns a well formatted String including all attributes.



**5 (20 points / 5 points each)** Create the Java class **Giraffe** that inherits from the **Animal** class. The **Giraffe** class has the following **private** attributes:

Attribute	neckLength : int	height : double	foods : String[]
-----------	------------------	-----------------	------------------

- a. Create a **default constructor** that calls the parent constructor and initializes all 3 attributes to the following values

Attribute	neckLength	height	foods
Default Value	0	0.0	Length of 3

- b. Create an **overloaded constructor** that takes in values for all 3 attributes as well as the attributes of the parent class' constructor and pass them to the parent constructor or assign them accordingly.

- c. Create a **helper method** that determines the equality of two String arrays and returns a boolean, by comparing the value at each index location. Return true if all elements of the arrays matches, return false if there is any mismatch. (Note: this method will be used by the equals method in part e)

```
private boolean doArraysMatch(String[] a, String[] b) {
```

```
}
```


- d. Create a **helper method** that returns the array of foods as a comma separated String.

```
private String getFoodsAsString() {
```

```
}
```

- e. Create the **equals** method. Remember to include the super class's **equals** method. Two Giraffe objects are equal when all their attributes are the same. (Note: be sure to use the helper method from part c)

- f. Create the **toString** method so that it returns a String including all attributes from both the parent and child classes. (Note: be sure to use the helper method from part d)






6 (10 points) Remember the recursive Searching algorithm BinarySearch. Write a recursive method to search for a target character in the array and return the index location if found or -1 if it is not found.

```
public static int binarySearch(char target, char[] theValues, int firstIndex, int lastIndex) {
```

```
}
```

7 (35 points / 7 points each) Write the code to create a GUI based class **TemperatureConverter** which inherits from **JFrame** and implements the **ActionListener** interface.



- a. Create the **constructor** so that the JButtons have listeners attached, and all components are added to the appropriate JPanel.

- b. Create the **getDoubleFromTextField** method that takes in a JTextField and returns the value it contained as a double it should handle exceptions appropriately within the method.

```
public double getDoubleFromTextField(JTextField jtf) throws Exception {
```

```
}
```

- c. Create the method `convertTemp` that takes in a temperature as a double, and the unit as a char that we are converting from. It should return the converted temperature as a formatted String (`"%.2f", tempF + " F"`) or (`"%.2f", tempC + " C"`)

Example:      `convertTemp(100.0, 'C')`              returns      `"212.00 F"`  
                 `convertTemp(87.0, 'F')`      returns      `"30.56 C"`

The conversion formulas are:

$$F = (C * 9.0/5.0) + 32.0$$

$$C = (F - 32.0) * 5.0/9.0$$

```
public String convertTemp(double temperature, char unit) {
```

```
}
```

- d. Create the **actionPerformed** method so that it determines which button was clicked and updates the `lblOut` with the conversion sentence shown in the example.

- e. Create a method `addConversionToFile` that appends a conversion to an output file named **temperatures.txt** for the examples given in 7c, the file would have:

```
100.0 C = 212.00 F  
87.0 F = 30.56 C
```

```
public void addConversionToFile(String conversion) {
```

```
}
```